

HOT WATER TANK WITH COIL

- ✓ European standards (CE)
- ✓ Factory produce and manage according to ISO 14100:2015
- ✓ Absolutely safe when operating
- ✓ Easy installation and use
- ✓ Absolute heat insulation
- ✓ Optimal capacity according to usage needs
- ✓ Powder coated/Stainless steel



5-year warranty



European standards



MODEL		HEV 100WT	HEV 150WT	HEV 200WT	HEV 300WT	HEV 500WT	HEV 1000WT	
Material of inner tank	/	SS304/SS316 - for Sea water and Mineral water						
Thickness of inner tank	mm	1	1	1.2	1.35	1.5	2	
Diameter of inner tank	mm	Φ370	Φ370	Φ420	Φ470	Φ600	Φ800	
Isulation layer	mm	High density polyurethane D = 50						
Outer shell	mm	Powder coated steel/Stainless Steel						
Magnesium rod	mm	Yes						
Diameter of inlet/outlet pipe	/	DN15/DN20						G1"(DN25)
Heater Booster	/	2 - 3 - 5 kW/220V/380V - Option						
Diameter of circulating pipe	/	DN20						G1"(DN25)
Relief Valve	/	DN15						G1"(DN25)
Operating pressure	/	0.6 Mpa						
Max running pressure	/	1.2 Mpa						
Unit size	mm	Φ480*1000	Φ480*1400	Φ550*1400	Φ580*1740	Φ700*1850	Φ900*2000	
Material of coil	/	SS304/SS316 - for Sea water and Mineral water						
Thickness/Diameter of coil	/	1mm/Φ16						
Length of coil	m	15		18		25	30	